

# SNOW RABBIT 3X

## TECHNICAL SPECIFICATIONS





# SNOW RABBIT 3X

## SPECIFICATIONS

DIMENSIONS		
Overall length (without blade)	3450 mm	135.8 in
Overall Length (with blade)	4200 mm	165.3 in
Overall length (with blade and tiller)	5600 mm	220.4 in
Overall width	2200 mm	86.6 in
Overall heigth	2360 mm	92.9 in
Weight (with Large 6-way blade)	2374 kg	5233 lb
Weight (with 12-way blade)	2408 kg	5308 lb
Weight (with Large 6-way blade + Large tiller)	2557 kg	5637 lb
Weight (with 12-way blade + Large tiller)	2591 kg	5712 lb
Max transportable weight on rear deck	750 kg	1653 lb

ENGINE		
Make	FCA/VM engines	
Model	R754EU 6EH	
Type	Turbo diesel electronic fuel system	
Emission	EPA Tier 4 final / EU Stage 5	
Number of cylinders	4	
Displacement	3.0 L	
Power @ 2600 rpm	134 hp	100 kW
Torque @ 1200 rpm	500 Nm	
Exhaust after treatment system	DOC + DPF + SCR	
Glow plug starter	yes	
Tank capacity	88 l.	23.2 US gal
Tank capacity DEF (AdBlue)	16 l.	4.2 US gal

DRIVING CHARACTERISTICS		
Speed, continuously variable	0- 25 km/h	0 – 15 mp/h
Turning radius	0°	
Spec. Ground pressure with blade	53 g/cm2	0.75 psi
Driving system	Steering joystick with 2nd speed set and cruise control	

WHEELS		
Quantity	8 wheels, 2 sprockets	
Type	solid	
TRACKS		
Standard tracks	Aluminium cleats with steel ice-spikes, PU tire guide	
All-season tracks (optional)	PU-covered alu cleats with optional 5 Pin Icepicks	
Width	785mm	30.9 in
Middle rut	142 mm	5.5 in

ELECTRICAL	
Voltage	12V
Battery	110 Amp/h
CAB (standard features)	
2-seat tiltable cab, ROPS certificated	
Manual heater with adjustable temperature, fan control	
Integrated sunroof	
Heated rear mirrors	
DAB+ radio with Bluetooth and USB port	
LED lighting system	
Beacon light, electric horn, back-up alarm, emergency parking brake with automatic application on door opening, fire extinguisher	
CAN-bus display	
Joystick for front/rear implement control	
(optional) Rear view camera with onboard display	

PASSENGER REAR CAB (optional)		
Insulated rear cabin for 6 persons, ROPS certified		
(optional) Ski rack; separately adjustable heating		

BLADES		
LARGE 6-WAY BLADE		
6 Hydraulic adjustments + 2 mechanic adjustment (tilt)		
Hydraulical tilt adjustment as option		
Width	2200 mm	86.6 in
LARGE 12-WAY BLADE		
10 hydraulic adjustments + 2 mechanic adjustment (tilt)		
Hydraulical tilt adjustment as option		
Width	2400 mm	94.4 in

HYDRAULIC TILLER		
LARGE TILLER		
Width with flaps	2800 mm	110.2 in
Working shaft width	2200 mm	86.6 in
Weight	183 kg	403 lb
Max rotating speed	2000 rpm	
Hydraulically driven cutting edge (optional)		
Up to 2 independent track setters with hydraulically adjustable depth		

COMPACTOR BAR		
Width	2400 mm	94.4 in
Hydraulically adjustable depth		
Mechanically adjustable cutting edge		

